

<b>Journal:</b>	Canadian Geotechnical Journal
<b>Title of paper:</b>	Relationship between electrical resistivity and basic geotechnical parameters for marine clays
<b>Names of authors:</b>	Michael Long <sup>1</sup> , Shane Donohue <sup>2</sup> , Jean-Sebastien L'Heureux <sup>3,4</sup> , Inger-Lise Solberg <sup>3</sup> , Jan Steinar Rønning <sup>3,5</sup> , Romaric Limacher <sup>1</sup> , Peter O'Connor <sup>6</sup> Guillaume Sauvin <sup>4,7,8</sup> , Magnus Rømoen <sup>9</sup> and Isabelle Lecomte <sup>4,7</sup>
<b>Affiliation of authors:</b>	1: University College Dublin (UCD), Ireland 2: University of Bath, UK (formerly UCD) 3: Geological Survey of Norway (NGU), Trondheim, Norway 4: International Centre for Geohazards (ICG) at NGI, Oslo, Norway 5: Norwegian University of Science and Technology (NTNU), Trondheim, Norway 6: APEX Geoservices, Gorey, Co. Wexford, Ireland 7: NORSAR, Kjeller, Norway 8: University of Oslo (UiO), Norway 9: Norwegian Geotechnical Institute (NGI), Oslo, Norway
<b>Corresponding author:</b>	Mike Long, Department of Civil, Structural and Environmental Engineering, University College Dublin, Newstead Building, Belfield, Dublin 4, Ireland Phone: +353-1-7163221 Fax: +353-1-7167399 e-mail: Mike.Long@ucd.ie
<b>Paper originally written:</b>	February 2012

**Title:** Relationship between electrical resistivity and basic geotechnical parameters for Norwegian clays

**Abstract:** Recently considerable efforts have been made in attempting to map quick clay areas using electrical resistivity measurements. However there is a lack of understanding on what soil parameters control the measured resistivity values. In order to address this issue inverted resistivity values from fifteen marine clay sites in Norway have been compared to basic geotechnical index properties. It was found that the resistivity value is strongly controlled by the salt content of the pore fluid. Resistivity decreases rapidly with increasing salt content. There is also a relatively clear trend of decreasing resistivity with increasing clay content and plasticity index. Resistivity values become very low ( $\approx 5 \Omega\text{m}$ ) for high clay content (>50%), medium to high plasticity ( $I_p \approx 20\%$ ) materials with salt content values greater than about 8 g/l (or corresponding remoulded shear strength values greater than 4 kPa). For the range of values studied there is poor correlation between resistivity and bulk density and between resistivity and water content. The data studied suggests that the range of resistivity values corresponding to quick clay is 10  $\Omega\text{m}$  to 100  $\Omega\text{m}$ , which is consistent with other published limits. A comparison is made between 2D ERT and RCPTU data for two of the sites and the two sets of data show similar trends and values irrespective of scale effect.

**Key words:** marine clay; quick clay; geophysics; resistivity; laboratory testing; Norway

## **Introduction**

In recent years considerable efforts have been made in Norway and Sweden into mapping of quick clay formations using combined geotechnical and geophysical methods. Although it was recognised that some intrusive geotechnical investigations will always be necessary the objective of these studies was to develop techniques to maximise the use of non intrusive relatively simple geophysical surveys such as Electrical Resistivity Tomography (ERT). For example Solberg et al. (2008), (2012) and Lecomte et al. (2008a) describe the use of resistivity measurements for mapping quick clay at landslide areas at Buvika, mid Norway, Rødde, mid Norway and Finneidfjord, northern Norway respectively. Donohue et al. (2011) and Pffaffhuber et al. (2010) detail integrated geophysical work with similar objectives for a site at Smørgrav in Southern Norway and Sauvin et al. (2011) outline comparable work at an adjacent site at Vålen. Similar work in Sweden has been published by Dahlin et al. (2005), Lundström et al. (2009) and Löfroth et al. (2011).

Parallel work has been carried out on use of the resistivity cone penetration test (RCPTU) in quick clay areas in both Norway by e.g. Rømoen et al. (2010) and in Sweden by Dahlin et al. (2004), Schälin and Tornborg (2009) and Löfroth et al.(2011).

Although most recent research effort on this topic have taken place in Scandinavia, quick clays continue to pose a hazard in other countries such as Canada (Geertsema and Torrance, 2005) and Japan (Torrance and Ohtsubo, 1995).

Perhaps not surprisingly these studies found that there is no simple correlation between resistivity and sensitivity, as they can be influenced by factors such as the density, water content, silt fraction, the fabric and structures of the soil, the chemistry of the pore fluid and the mineralogy of the clay particles.

The objective of the present work is to investigate the influence of the basic index parameters of Norwegian clays on the measured resistivity values in order to obtain a deeper

understanding of what controls the values. The ultimate intention is to provide assistance to practicing engineers in the interpretation of resistivity surveys in marine clay areas.

In this study clay properties from geotechnical testing are compared to resistivity data, mainly from ERT, at fifteen sites. At three of the sites (Rissa, Finneidfjord and Kattmarka) large destructive quick clay landslides had occurred, see Gregersen (1981) and L'Heureux et al. (2011a), Longva et al. (2003) and L'Heureux et al. (2011b), Nordal et al. (2009) and Solberg et al. (2011).

## The Sites

The location of the sites is shown on Figure 1. The sites are all located in coastal areas of Norway coinciding with those locations underlain by elevated marine clays. The sites may be grouped as follows:

- Southern Norway: E16 Kjørby – Wøyen, Skøyen – Asker, RVII – Hilleren, Drammen – Museumpark, Farriseidet, Skienselven, Månejordet, Smørgrav and Vålen,
- Mid Norway: Berg, Rissa, Rødde and Buvika and
- North Trøndelag and Northern Norway: Finneidfjord and Kattmarka.

A summary of the soil properties at the fifteen sites surveyed is given on Table 1. The clay is characterised by water content ( $w$ ) of 20% to 50%, unit weight ( $\gamma$ ) of 17 kN/m<sup>3</sup> to 20.5 kN/m<sup>3</sup>, relatively high clay content (10% to 50%), low to medium plasticity ( $I_p$  in range 2% to 30%) and of soft to firm consistency (undrained shear strength  $s_u$  in the range 10 kPa to 40 kPa). Sensitivity ( $S_t$ ) is the most variable parameter varying from 2 to extremely high values of the order of 350. The exception is the Farriseidet site which is underlain by organic clay of low unit weight and high water content.

## **Electrical Resistivity Tomography (ERT)**

### **Background**

The use of 2D resistivity measurements as a tool for identifying sub surface profiles has expanded during the last 10 years due to advances in the measurement technique and the data acquisition and processing software. The development has also been driven by the relatively high cost of traditional drilling and sampling techniques. 2D resistivity measurements give a continuous and relatively detailed picture of the subsurface within a short time. In an area without previous investigations the 2D resistivity method gives an overview of the subsurface as a basis for further investigation and for the determination of optimal locations for drilling. The method is a cost effective and valuable complement to drilling as it can separate intact marine clay deposits (high salt content / low resistivity) from quick clay (low salt content / higher resistivity), in addition to identifying coarser material and bedrock. Typical resistivity values for various materials are summarised on Table 2, which is modified from Solberg et al. (2012)

### **Equipment and data acquisition**

The ERT surveys at eight of the nine southern Norway sites were carried out by APEX Geoservices / UCD. The exception is Vålen where the work was done by the Norwegian Geotechnical Institute (NGI). The work at the six sites in mid Norway and northern Norway was performed by the Geological Survey of Norway (NGU).

Similar techniques were used at all sites. For the APEX / UCD surveys data was acquired using a multi-electrode Campus Tigre resistivity meter with a 32 takeout multicore cable and 32 conventional stainless steel electrodes. An electrode spacing of 3 m was used as default. However at several of the sites a 5 m spacing was also used to provide deeper data (e.g. at E16 Kjørby – Wøyen and RVII- Hilleren). As the subsurface layers were not expected to deviate significantly from the horizontal a four electrode Wenner array configuration was

used to acquire multiple readings for each ERT profile. The Wenner array also generally provides a good signal to noise ratio (Donohue et al., 2011).

The work at Vålen employed a Terrameter LS with four cables of 21 takeouts (81 active electrodes). A roll-along gradient configuration with 2 m and 4 m electrode spacing was used to acquire the data, leading to a total profile length of 160 m to 320 m.

The equipment used by NGU was the Lund system, developed by Dahlin (1993), comprising a relay box (ABEM ES10-64) and four multi-electrode cables and 81 active stainless steel electrodes, controlled by an ABEM Terrameter SAS 4000. The distance between the electrodes was generally 5 m and occasionally 2 m or 10 m. Use was made of both the Wenner and Gradient array systems. The Gradient array can yield up to seven times more data than the Wenner array in a shorter time and thus can be useful for examining lateral changes in resistivity (Dahlin and Zhou, 2006).

### **Data processing**

In all cases the data processing and inversion was carried out using the software Res2Dinv (Loke, 2007). This software uses a forward modelling subroutine to calculate the apparent resistivity values and a non-linear least-squares optimisation technique (Loke and Barker, 1996). In a study of synthetic data to represent marine clays, Reiser et al. (2010) showed that “smooth” inversion with a vertical / horizontal filter of 0.5 resulted in the most accurate inversion models. “Smooth” inversion was generally used as standard (Solberg et al., 2012) but it was found that “robust” inversion can give better definition of sharp boundaries, e.g. between clay and bedrock (Reiser et al., 2010).

As there occasionally was a large subsurface resistivity contrast the Gauss- Newton method was used for first 2 to 3 iterations then the quasi- Newton method was employed. This was found to provide the best compromise between computational time and accuracy

(Loke and Dahlin, 2002). Most inversions performed converged to RMS errors of less than 6% within 5 to 6 iterations and the final RMS errors were usually less than 1.5%.

## RESULTS AND CORRELATIONS

Inverted resistivity values were extracted from the Res2Dinv data files and compared to the geotechnical parameters from the same depth. In each case a resistivity profile and a matching borehole, i.e. a borehole on same line as the resistivity section or located at most 5 m from the section, was used.

### Resistivity and salt content of pore fluid

The relationship between resistivity and salt content of the pore fluid is shown on Figure 2. Unfortunately as salt content is not measured routinely in all investigations the amount of data is relatively limited. As expected the link between these two parameters is strong. Resistivity decreases rapidly with increasing salt content and reaches a low values of about 5  $\Omega\text{m}$  and becomes more or less constant once the salt content exceeds approximately 8 g/l. The exponential trendline shows a relatively good coefficient of correlation  $R^2$  value of 0.8.

In the past authors such as Bjerrum (1954) and Rosenqvist (1955) have suggested that clay becomes quick (i.e. sensitivity  $S_t > 30$  and remoulded shear strength  $s_{ur} < 0.5 \text{ kPa}$ ) when the salt content is less than 5 g/l. Subsequently Torrance (1974) suggested the limit should be 2 g/l. The plot of sensitivity versus salinity of the pore fluid, shown on Figure 3, shows that although all of the quick clay data points have salt content less than 5 g/l there are also a significant number of data points with salt content less than 2 g/l or 5 g/l for which the sensitivity is less than 30. In addition Andersson-Sköld et al. (2005) measured a salinity of 5.6 g/l in Swedish quick clay. Non quick marine clay may also contain very low salt content due to continued leaching or weathering.

This illustrates that although salt content of the pore fluid is a very important controlling factor, sensitivity of marine clay is also influenced by other factors (Mitchell, 1993).

### **Resistivity and clay content**

The relationship between resistivity and clay content is shown on Figure 4. There is a relatively strong correlation between the two properties with resistivity decreasing with increasing clay content. This finding is as expected as clay particles facilitate surface conductance of electrical current. Those sites with relatively low clay content (e.g. the comparatively silty materials at Finneidfjord, Kattmarka and Rødde) show high resistivity values. Beyond clay content of about 40% (by mass) the resistivity values are generally low. The polynomial trendline shown has a reasonable  $R^2$  value of 0.59.

### **Resistivity and plasticity index**

A similar pattern, to that of clay content, emerges in the plot of resistivity against plasticity index ( $I_p$ ) on Figure 5. Note there are unfortunately relatively few data points for high plasticity clays with  $I_p > 20\%$ . Again there is a reasonably strong trend of reducing resistivity due to increasing  $I_p$ . This is consistent for the finding for clay content above as  $I_p$  will increase with increasing clay content. Beyond an  $I_p$  value of about 20%, corresponding to the upper limit of medium plasticity (Norsk Geoteknisk Forening, (NGF, 1982) the resistivity values are low ( $\approx 5 \Omega m$ ) and more or less constant. For the low plasticity materials the resistivity values are generally higher but are more scattered. Some attempts were made to fit a trendline through the data but the resulting  $R^2$  value was poor.

### **Resistivity and remoulded shear strength**

As remoulded shear strength ( $s_{ur}$ ) is directly related to the salt content of the pore fluid, one would expect a strong link between resistivity and  $s_{ur}$  (as measured by the fall cone). As seen on Figure 6 resistivity decreases rapidly with increasing remoulded shear strength and becomes more or less constant when the  $s_{ur}$  value exceeds 4 kPa. The reasons for the relatively high values at the RVII - Hilleren site are unclear and warrant further study.

Remoulded shear strength values in silty materials needs to be treaded with caution as the shearing action may not be totally undrained leading to possible relatively high values.

On Figure 7, the focus is on those values where  $s_{ur}$  is less than 0.5 kPa, which is the threshold for quick clay according to NGF (1982). There is a clear trend of decreasing resistivity with increasing  $s_{ur}$ . Solberg et al. (2012) reviewed a large body of data and found that 10  $\Omega\text{m}$  to 100  $\Omega\text{m}$  represented the resistivity range for quick clay. Although most of the data discussed here is within this range, some of the sites with relatively high silt content (e.g. (Skien selven, Rødde and Kattmarka) exhibit significantly higher resistivity values up to 150  $\Omega\text{m}$ .

### **Resistivity and sensitivity**

Resistivity values are plotted against sensitivity (from the fall cone) on Figure 8. There is a good relationship between the two properties with resistivity increasing more or less linearly with sensitivity. The increase in scatter of the data with increasing  $S_t$  is due to the decreasing accuracy of the fall cone measurements.

The high values for Skien selven, Rødde and Kattmarka are due to the silty nature of the material as presented above. The relatively high values for RVII need to be investigated further.

### **Resistivity and bulk unit weight**

The relationship between resistivity and bulk unit weight is shown on Figure 9. Intuitively one would expect resistivity to decrease with increasing unit weight (or density) as the particles are forced closer together. For the bulk of the data, where the resistivity is less than 50  $\Omega\text{m}$ , there is some weak tendency for decreasing resistivity with increasing bulk unit weight. However the trends are far from clear and vary from site to site. For example the Rissa data follows the expected trend whereas the Smørgrav data shows the opposite

tendency. Some sites, for example Skøyen – Asker, show relatively constant resistivity for a range of unit weight values.

The higher resistivity values recorded for the sites at Skienselven, Finneidfjord and Kattmarka fall outside the general trend and can be attributed to the silty nature of these materials. The Farriseidet site shows low bulk unit weight values due to the organic nature of the material.

It would seem that, although bulk unit weight plays a role in the resulting measured resistivity, its influence is outweighed by other factors.

### **Resistivity and water content**

Inverted resistivity values are plotted against water content on Figure 10. There is no clear pattern in the plot, even for the main body of the data where the resistivity is less than 50  $\Omega\text{m}$ . Similar to the relationship with bulk unit weight, the values for the materials with either high silt / sand content or high organic content fall well away from the main body of the data.

## **DISCUSSION**

The data presented above shows that the measured resistivity values depend on a number of interrelated factors. It is difficult to separate the influence of each individual parameter. In Figure 8, for example, an attempt has been made to do this, where the clay content values have been superimposed on the plot of resistivity against sensitivity. Although the higher clay content materials correspond to the lower resistivity values there is insufficient data or insufficient trends to plot, e.g. contours of clay content on the diagram.

The data shows that resistivity is strongly influenced by the salt content of the pore fluid and also influenced significantly by the clay content and plasticity of the material. It could be argued that the data for clay content and plasticity index on Figures 4 and 5 merely reflect reducing salt content. However these figures contain more data than shown on Figure 6 and include data for sites where the remoulded shear strength (and hence salinity) are similar.

For the data available no relationship was found between resistivity and water content. However as the range of values studied here is relatively limited, and many other studies have shown the importance of water content on measured resistivity, this finding will not be universally applicable.

The data presented in this study compares point data (laboratory measurements) with larger soil volumes (geophysical data) and scale effects may therefore arise. The influence of such scale effects may be studied by comparing ERT data with the previously mentioned resistivity cone penetration test (RCPTU). The latter involves an 80 cm long, 4.4 cm diameter module on which four ring electrodes are mounted. The two outer rings apply current and the two inner rings measure the voltage. The distance between the two outer rings is approximately 20 cm, and thus the RCPTU measurements relate to a small body of soil similar in scale to a soil sample.

Figure 11 shows a comparison of ERT and RCPTU data from tests sites at Rissa (Fig 11a) and b) and Rødde (Figure 11c). The data are taken from Solberg et al. (2010) and (2012) respectively. The two sets of data for Rissa show that the RCPTU data can give either lower or higher resistivity values than for the ERT data. Overall the relationship between the two sets of data at both sites is very good and confirms the reliability and applicability of the ERT data for the present purposes.

2D ERT data measured at the surface, may suffer from some methodical weaknesses. Effects of 3D geology may influence on the measured resistivity values and consequently on the inverted 2 D resistivity section. In addition the principles of equivalence and suppression may influence on the inverted sections (Reynolds, 2011). Equivalence appears when resistivity in one layer lies between the resistivity of the surrounding layers while equivalence appears on ascending or descending resistivity towards the depth. Anisotropic resistivity may also influence on the results when data from different methods are compared. The effects of

these weaknesses are non unique inversion results. Nonetheless the comparison between ERT and RCPTU data, shown on Figure 11, confirms there is a good correlation between 2D surface and 1D borehole resistivity data. However, in detail there are deviations that make it necessary to have great and partly overlapping intervals for the resistivity in different materials in an interpretational model. The present study will give a better understanding on what kind of geotechnical information that can be extracted from the resistivity data.

## CONCLUSIONS AND RECOMMENDATIONS

The ultimate objective of this work was to provide assistance for practicing engineers in the interpretation of resistivity surveys in glacio-marine and marine clay areas by studying the influence of basic geotechnical parameters on resistivity values from 2D measurements. It was found that:

1. There is a strong link between resistivity and both salt content of the pore fluid and remoulded shear strength. Resistivity decreases rapidly with increasing salt content or remoulded shear strength. The resistivity values become more or less constant if the salt content is greater than about 8 g/l and the remoulded shear strength is greater than 4 kPa.
2. There is also a relatively good trend of decreasing resistivity with increasing clay content and plasticity index. For high plasticity clays, with  $I_p \approx 20\%$  and clay content  $> 50\%$ , the measured resistivity values are very low ( $\approx 5 \Omega\text{m}$ ).
3. It would seem that, although bulk density plays a role in the resulting measured resistivity; its influence is outweighed by other factors such as salt content of the pore fluid and clay content.
4. The data presented here suggest that the range of resistivity values corresponding to quick clay is  $10 \Omega\text{m}$  to  $100 \Omega\text{m}$ , and this is consistent with other published

limits. Thus ERT surveys alone are not sufficient for mapping quick clay and need to be supplemented with conventional drilling and sampling.

5. A comparison of ERT and RCPTU show comparable trends and similar resistivity values. This confirms that the ERT data, which represent bulk resistivity, can give sufficiently accurate information on local soil conditions.

For future work it would be useful to:

- Extend the range of clays studied into those of higher plasticity,
- Carry out additional work on silt sites to examine the controlling factors on resistivity for these materials,

## Tables

Table 1. Summary of soil types and material properties for sites surveyed. (See separate document).

Extra refs: Long et al. (2009), Bjerrum (1967) , Lunne and Lacasse (1999), Rømoen (2006), Gregersen (1981), Aasland (2010), Ottesen (2009), Lecomte et al. (2008b), Solberg et al. (2011), Helle (2004), Multiconsult (2009)

**Table 2:** Typical resistivity values for various materials modified from Solberg et al. (2012)

Resistivity ( $\Omega\text{m}$ )	Main characterisation	Description
1-10	Unleached marine clay deposits	The clay has been exposed to little leaching since deposition. The pores in the clay still contain salt water, which stabilise the structure. Because of the large concentration of ions in the pore water, the conductivity of the clay is good, and thus the resistivity values are low
10-100	Leached clay deposits	Sensitive clay develops as groundwater leaches ions from the marine clay. The electrical conductivity of the deposit is still high, but not as good as for the unleached marine clay. Other sediment features can give resistivity values similar to those of quick clay: further leached marine clay (not quick anymore), silt, and fine-grained till
> 100	Dry crust clay deposits, coarse sediments, (bedrock)	Dry crust clay; remoulded, dry clay from quick-clay landslides; and coarser materials like sand and gravel will have higher resistivity values than marine clay. Most bedrock types will have values of several thousand $\Omega\text{m}$ .

## Summary of Figures

Figure No.	Description	File
		DELL/Papers/CanGeoJnl/ERTNorway/ DELL/Reports/ERTNorwayHøst2010/
1	Site locations	Norge.tiff
2	Resistivity and salt content of pore fluid	Resagainstsalt.grf

3	Sensitivity and salt content of the pore fluid	Stagainstsalt.grf
4	Resistivity and clay content	Resagainstclay.grf
5	Resistivity and plasticity index	Resagainstplasticity.grf
6	Resistivity and remoulded shear strength	Resagainstsur.grf
7	Resistivity and remoulded shear strength less than 0.5 kPa	Resagainstsurlessthan0.5kPa.grf
8	Resistivity and sensitivity	ResagainstSt.grf
9	Resistivity and bulk unit weight	Resagainstbulkdensity.grf
10	Resistivity and water content	Resagainstwatercontent.grf
11	Comparison of ERT and RCPTU for Rissa and Rødde	ERTvsRCPTU.jpg

## References

- Aasland, R. (2010) "Kartlegging av kvikkleire med 2D resistivitet og RCPT i Rissa," *Masteroppgave, Institutt for Geoteknikk*. Trondheim: NTNU Trondheim (In Norwegian).
- Andersson - Sköld, Y., J.K. Torrance, B Lind, K. Odén, R.L. Stevens, and K. Rankka (2005) "Quick clay - A case study of chemical perspective in southwest Sweden," *Engineering Geology*, Vol. 82, pp 107 - 118.
- Bjerrum, L. (1954) "Geotechnical properties of Norwegian marine clays," *Géotechnique*, Vol. 4, No. 1, pp 49 - 69.
- Bjerrum, L. (1967) "Engineering geology of Norwegian normally consolidated marine clays as related to settlement of buildings," *Géotechnique*, Vol. 17, No. 2, pp 81-118.
- Dahlin, T. (1993) "On the automation of 2D resistivity surveying for engineering and environmental applications," *PhD Thesis Department of Engineering Geology* Lund University of Technology Sweden.
- Dahlin, T., R. Larsson, V. Leroux, and K. Rankka (2005) "Resistivity imaging for mapping of quick clays for landslide risk assessment," *Near Surface 2005 - 11<sup>th</sup> European Meeting of Environmental and Engineering Geophysics* Palermo, Italy.
- Dahlin, T., M. Palm, and H. Garin (2004) "Combined resistivity imaging and RCPT for geotechnical preinvestigation," *14th NGM, Nordic Geotechnical Meeting*. Ystad, Sweden, pp C81 - C88.
- Dahlin, T., and B. Zhou (2006) "Multiple-gradient array measurements for multi-channel 2D resistivity imaging," *Near Surface Geophysics*, Vol. 4, pp 113 - 123.
- Donohue, S., M Long, P. O'Connor, T. Eide-Helle, A.A. Pffaffhuber, and M. Rømoen (2011) "Geophysical mapping of quick clay: a case study from Smørgrav, Norway," *Journal of Near Surface Geophysics, EAGE*, Vol. In Press.
- Geertsema, M., and J.K. Torrance (2005) "Quick clay from the Mink Creek landslide neat Terrace, British Columbia: Geotechnical properties, mineralogy and geochemistry," *Canadian Geotechnical Journal*, Vol. 42, No. 3, pp 907 - 918.
- Gregersen, O. (1981) "The quick clay landslide at Rissa, Norway," *Norwegian Geotechnical Institute Publication*, Vol. 135, pp 1 - 6.
- Helle, T.E. (2004) "E39 Vigda, Buvika, Profile 3 - Natural Slope," *Projectoppgave, Institutt for Geoteknikk*. Trondheim: NTNU.
- L'Heureux, J.-S., R.S. Eilertsen, S. Glimsdal, D. Issler, I.-L. Solberg, and C.B. Harbitz (2011a) "The 1978 quick clay landslide at Rissa, mid Norway: subaqueous morphology and tsunami simulations," In: Y. Yamada et al., Ed., *5th International Symposium on Submarine*

*Mass Movements and Their Consequences.* Kyoto, Japan: Springer Science + Business Media.

L'Heureux, J.-S., O. Longva, A. Steinar, L. Hansen, M.E. Vardy, M. Vanneste, H. Haflidason, J. Brendryen, T.J. Kvalstad, C.F. Forsberg, S. Chand, and A. Kopf (2011b) "Identification of weak layers and their role for the stability of slopes at Finneid fjord, Northern Norway," In: Y. Yamada et al., Ed., *5th International Symposium on Submarine Mass Movements and Their Consequences*. Kyoto, Japan: Springer Science + Business Media, pp 321 - 330.

Lecomte, I., M. Bano, S.-E. Hamran, E. Dalsegg, and K.M. Nielsen (2008a) "Mapping quick clay sites for geohazard assessment: the Finneid fjord case study, Norway," *Near Surface 2008 - 14<sup>th</sup> European Meeting of Environmental and Engineering Geophysics* Kraków, Poland, p Paper B19.

Lecomte, I., M. Bano, S.-E. Hamran, E. Dalsegg, K.M. Nielsen, M.H. Nielsen, G. Douillet, E. Frery, A. Guy, and S. Volesky (2008b) "Submarine slides at Finneid fjord (Norway): geophysical investigations," *21st EEGS Symposium on the application of geophysics to engineering and environmental problems*, pp 376 - 388.

Löfroth, H., P. Suer, T. Dahlin, V. Leroux, and D. Schälin (2011) "Quick clay mapping by resistivity - Surface resistivity, CPTU-R and chemistry to complement other geotechnical sounding and sampling," *Statensgeotekniskainstitut, SGI. Götaälvtredningen. GÄU. Delrapport 30.* Linköping: Swedish Geotechnical Institute.

Loke, M.H. (2007) "Res2DInv ver. 3.56. Geoelectrical Imaging 2D and 3D. Instruction Manual. Geotomo Software."

Loke, M.H., and R.D. Barker (1996) "Rapid least-squares inversion of apparent resistivity pseudosections by quasi Newton method," *Geophysical Prospecting*, Vol. 44, pp 131-152.

Loke, M.H., and T. Dahlin (2002) "A comparison of Gauss-Newton and quasi Newton methods in resistivity imaging inversion," *Journal of Applied Geophysics*, Vol. 49, No. 3, pp 149-162.

Long, M., N. El Hadj, and K. Hagberg (2009) "Quality of conventional fixed piston samples of soft clay," *Journal of Geotechnical and Geoenvironmental Engineering, ASCE*, Vol. 135, No. 2, p 185.

Longva, O., N. Janbu, L.H. Blikra, and R. Bøe (2003) "The 1996 Finneid fjord slide: seafloor dynamics," *First International Symposium on Submarine Mass Movements and their Consequences EGS-AGU-EUG Joint Meeting*. Nice, France: Kluwer Academic Publishers, pp 531 - 538.

Lundström, K., R. Larsson, and T. Dahlin (2009) "Mapping of quick clay formations using geotechnical and geophysical methods," *Landslides*, Vol. 6, No. 1, pp 1 - 15.

Lunne, T., and S. Lacasse (1999) "Geotechnical characterisation of the low plasticity Drammen clay," In: T. Tsuchida, and A. Nakase, Eds., *Proceedings of the International Symposium on Characterisation of Soft Marine Clays - Bothkennar, Drammen, Quebec and Ariake clays*. Yokosuka: A.A. Balkema, Rotterdam, pp 33-56.

Mitchell, J. K. (1993) *Fundamentals of soil behaviour*, New York Wiley.

Multiconsult (2009) "Kattmarken boligfelt, grunnundersøkelser. Geoteknisk datarapport med orienterende geoteknisk vurdering," Multiconsult Report No. 413456-1, dated 06.03.2009 (In Norwegian).

NGF (1982) "Veilding for symboler og definisjoner i geoteknikk - presentasjon av geotekniske undersøkelser." Oslo: Norwegian Geotechnical Society (Norsk Geoteknisk Forening) (In Norwegian).

Nordal, S., C. Alén, A. Emdal, L. Jendeby, E. Lyche, and C. Madshus (2009) "Skredet i Kattmarkvegen i Namsos 13. mars 2009. Rapport fra undersøkelsesgruppe satt ned av

- Samferdselsdepartementet," Institutt for Bygg, Anlegg og Transport, Faggruppe for Geoteknikk, NTNU (In Norwegian).
- Ottesen, H.B. (2009) "CPTU med resistivitetsmåling," *Masteroppgave, Institutt for Geoteknikk*. Trondheim: NTNU, Trondheim (In Norwegian).
- Pfaffhuber, A.A., M. Bastani, S. Cornée, M. Rømoen, S. Donohue, T.E. Helle, M. Long, P. O'Connor, and L. Persson (2010) "Multi - method high resolution geophysical and geotechnical quick clay mapping," *Near Surface 2010 - 16<sup>th</sup> European Meeting of Environmental and Engineering Geophysics* Zurich.
- Reiser, F., T. Dahlin, J.S. Rønning, and I.-L. Solberg (2010) "Resistivity modelling for clay layer characterisation, possibilities and limitations." Trondheim: Geological Survey of Norway (NGU) Report 2010.047.
- Reynolds, J.M. (2011) *An Introduction to Applied and Environmental Geophysics*: Wiley - Blackwell, UK.
- Rømoen, M. (2006) "Evaluation of stability and deformations in the Berg area Trondheim," *Masteroppgave, Institutt for Geoteknikk*. Trondheim: NTNU.
- Rømoen, M., A.A. Pfaffhuber, K. Karlsrud, and T.E. Helle (2010) "Resistivity on marine sediments retrieved from RCPTU soundings: a Norwegian case study," In: P.K. Robertson, and P.W. Mayne, Eds., *2nd International Symposium on Cone Penetration Testing (CPT '10)*. Huntington Beach, California: Omnipress, pp 289 - 296.
- Rosenqvist, I.T. (1955) "Investigations in the clay-electrolyte-water system," *Norwegian Geotechnical Institute Publication*, Vol. 9, p 36.
- Sauvin, G., S. Bazin, M. Vanneste, I. Lecomte, and A.A. Pfaffhuber (2011) "Towards joint inversion / interpretation for landslide-prone areas in Norway - integrating geophysics and geotechnique," *Near Surface 2011 - 17<sup>th</sup> European Meeting of Environmental and Engineering Geophysics* Leicester, UK, p Paper E11.
- Schälin, D., and J. Tornborg (2009) "Evaluation of CPT-R and resistivity measurements in quick clay area," *MSc Thesis, Department of Civil and Environmental Engineering, Division of GeoEngineering, Chalmers University of Technology*. Göteborg: Chalmers University of Technology.
- Solberg, I.-L., R. Aasland, E. Dalsegg, L. Hansen, J.-S. L'Heureux, and J.S. Rønning (2010) "Kvikkleireproblematikk i Rissa - bruk av resistivitetsmålinger," *Fjellsprengningsdagen, Bergmekanikk- og Geoteknikkdagen*. Oslo: Norsk Geoteknisk Forening (In Norwegian), p Chapter 37.
- Solberg, I.-L., E. Dalsegg, and L. Hansen (2011) "Resistivitetsmålinger for løsmassekartlegging i Namsos, Nord-Trøndelag. Data og tolknninger." Trondheim: Geological Survey of Norway (NGU) Report 2010.046 (In Norwegian).
- Solberg, I.-L., L. Hansen, J.S. Rønning, E.D. Haugen, E. Dalsegg, and J.F. Tønnesen (2012) "Combined geophysical and geotechnical approach to ground investigations and hazard zonation of a quick clay area, mid Norway," *Bulletin of Engineering Geology and the Environment*, Vol. 71, No. 1, pp 119 - 133.
- Solberg, I.-L., J.S. Rønning, E. Dalsegg, L. Hansen, K. Rokoengen, and R. Sandven (2008) "Resistivity measurements as a tool for outlining quick clay extent and valley-fill stratigraphy: a feasibility study from Buvika, central Norway," *Canadian Geotechnical Journal*, Vol. 45, pp 210-225.
- Torrance, J.K. (1974) "A laboratory investigation of the effect of leaching on the compressibility and shear strength of Norwegian marine clays," *Géotechnique*, Vol. 24, No. 2, pp 155 - 173.
- Torrance, J.K., and M Ohtsubo (1995) "Ariake Bay quick clays: A comparison with the general model," *Soils and Foundations*, Vol. 35, No. 1, pp 11 - 19.

Paper by Long et al. on: Relationship between electrical resistivity and basic geotechnical parameters for marine clays


**Table 1:** Summary of soil types and material properties for sites surveyed

Location	Soil type	Depth (m)	w (%)	$\gamma$ (kN/m <sup>3</sup> )	clay (%)	I <sub>p</sub> (%)	s <sub>u</sub> <sup>†</sup> (kPa)	S <sub>t</sub> * (%)	References
Southern Norway									
E16 Kjørby – Wøyen BH1054	0-2m dry crust, 2-15 m medium sensitive clay (organic?), 15 – 35m quick clay	2-15 15-35	20-55 30-40	16.5-19 17.5-19	6-21 46	9-18 6-9	35-45 20-55	8-23 >30	Rømoen et al. (2010)
E16 Kjørby – Wøyen BH1306	Soft clay medium sensitive	1.5-10.2	32-51	16.6-19	n/a	9-17	18-33	5-26	Rømoen et al. (2010)
Skøyen – Asker	0-2m dry crust, 2-5m low sensitive clay, 5- 16.5m (proven) quick clay	2-5 5-16.5	30-40 20-35	17.6-18.4 18.1-20.6	n/a	6 one value only	10-40 10-15	2-12 >80	NGI files
RVII - Hilleren	0-4 m dry crust, 4-15m, low sensitive clay, 15 – 26m (proven) medium sensitive clay	4-15 15-	31-42 33-38	18-19 17.5-19.5	30-44 40-45	11-21 5-13	10-35 5-25	3-9 5-30	Long et al. (2009)
Drammen - Museumpark	0-4m fine sand, 4-12m low sensitive plastic clay, 12 – 35 m lean clay	4-12 12-20	40-55 30	16.5-17 18.5-19.5	40-42 32-39	20-30 10	25-30 33-33	6-10 3-5	Bjerrum (1967), Lunne and Lacasse (1999)
Farriseidet	0-3m peat, 3-8m quick (organic?) clay, rock at 8m	0-3 3-8	>400 75-120	10.5 13.8-15.4	n/a 29-49	n/a 13-27	8 7-28	10 70-140	NGI files
Skienselven	0-6m silty sandy clay, 6-10.7m (proven) quick clay	6-10.7	26-33	19.1-19.7	n/a	3	10-24	110-240	NGI files
Månejordet	0-2m dry crust, 2-5.5m low sensitive sandy clay, 5.5- 14.5m quick clay	2.5-5.5 5.5-14.5	28-50 25-40	18-20.5 18-19.5	20 24-27	14-26 6-9	30-45 20-50	<10 50-350	Statens vegvesen / UCD files


Smørgrav	0-5m soft clay 5-13m quick clay 13-22m soft clay	0-5 5-13 13-22	27-42 38-45 39-46	17.9-18.5 17.8-18.3 17.8-18.2	41-57 37-44 53-58	13-14 10-15 20-22	37 19-25 24-28	19 23-63 5-6	Donohue et al. (2011), Pfaffhuber et al. (2010)
Vålen	Soft to firm low sensitive clay	3.2-22.2	37-47	18.2-19.6	36.6-39.4	16.4-20.3	12-34	2-15	Sauvin et al. (2011)
Mid Norway									
Berg	Firm to stiff low sensitive clay	3.6-17.6	23-32	19.8-20.6	n/a	6.6-10.5	39-82	4-10	Rømoen (2006)
Rissa H3-H4	Soft to firm clay medium sensitive	2.2-11.1	22-42	18.1-20	37-57	6-14	12-38.5	2-14.1	Gregersen (1981), Aasland (2000), L'Heureux et al. (2011a)
Rissa H5	Soft quick clay	2.4-10.9	28-40	18.3-19.8	47	7-12	9-38	13-61.5	Aasland (2000)
Rødde	Firm silty clay occasionally quick	1.5-20.5	26-33	19.1-19.7	30-47	n/a	28-71	2.5-37 65-235 occasionally	Ottesen (2009), Solberg et al (2011b)
Buvika	Firm quick clay	2.4-23.4	30-39	18.4-19.3	28-47	12-17	20-80	15-350	Solberg et al. (2008), Helle (2004)
North Trøndelag and Northern Norway									
Finneidfjord	Soft occasionally sandy clay	2.5-11.5	28-40	18.4-21.8	9-17	n/a	12-27	3-11	Lecomte et al. (2008a and 2008b) L'Heureux (2011b)
Kattmarka	Soft silty clay occasionally quick	1.2-19.6	26-38	18.5-19.7	24-35	6-9	9-48	4.8-67	Solberg et al. (2011a), Nordal et al. (2009), Multiconsult (2009)

**Figures for paper by Long et al.**


**Relationship between electrical resistivity and basic geotechnical parameters for marine clays**




**Fig 1.** Site locations




**Fig 2.** Resistivity and salt content of the pore fluid




**Fig 3.** Sensitivity and salt content of the pore fluid




**Fig 4.** Resistivity and clay content




**Fig 5.** Resistivity and plasticity index




**Fig 6.** Resistivity and remoulded shear strength




**Fig 7.** Resistivity and remoulded shear strength less than 0.5 kPa




**Fig 8.** Resistivity and sensitivity



**Fig 9.** Resistivity and bulk unit weight



**Fig 10.** Resistivity and water content



**Fig 11.** Comparison of 2D resistivity data (ERT) and RCPTU data from test sites at Rissa (a and b) and Rødde (c) (Data from Solberg et al., 2010 and 2011b)

oOo